




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : G11B 23/03, 23/033, 23/50	A1	(11) International Publication Number: WO 99/67785 (43) International Publication Date: 29 December 1999 (29.12.99)
(21) International Application Number: PCT/JP99/03247 (22) International Filing Date: 18 June 1999 (18.06.99) (30) Priority Data: 10/176894 24 June 1998 (24.06.98) JP (71) Applicant (for all designated States except US): FUJI PHOTO FILM CO., LTD. [JP/JP]; 210, Nakanuma, Minami-ashigara-shi, Kanagawa-ken 250-0123 (JP). (72) Inventors; and (75) Inventors/Applicants (for US only): <u>KATO</u> , Shinichi [JP/JP]; Fuji Photo Film Co., Ltd., 12-1, Oogi-cho 2-chome, Odawara-shi, Kanagawa-ken 250-0001 (JP). <u>MIZUTA</u> , Akira [JP/JP]; Fuji Photo Film Co., Ltd., 12-1, Oogi-cho 2-chome, Odawara-shi, Kanagawa-ken 250-0001 (JP). <u>HAYASHI</u> , Yoichi [JP/JP]; Fuji Photo Film Co., Ltd., 12-1, Oogi-cho 2-chome, Odawara-shi, Kanagawa-ken 250-0001 (JP). (74) Agents: YANAGIDA, Masashi et al.; Yanagida & Associates, 7F, Benex S-1, 3-18-20, Shin-Yokohama, Kohoku-ku, Yokohama-shi, Kanagawa-ken 222-0033 (JP).		(81) Designated States: CN, KR, US, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>With international search report.</i>

(54) Title: MAGNETIC DISC CARTRIDGE, METHOD OF MANUFACTURING THE SAME AND METHOD OF CLEANING LINERS OF THE SAME

(57) Abstract

A magnetic disc cartridge includes a casing formed of upper and lower shell halves mated together, a disc-like recording medium supported for rotation in the casing and a liner fixed to each of the inner surfaces of the upper and lower shell halves by ultrasonic welding by use of an ultrasonic welding horn. The liner has an outer contour defined by an outer peripheral edge, a central opening defined by an inner peripheral edge, and a slit-like cutaway portion defined by a pair of linear edges extending between the outer peripheral edge and the inner peripheral edge. The ultrasonic welding horn is provided with a welding pattern in the form of a protrusion pattern formed on a welding face thereof over the entire welding area in which the ultrasonic welding horn is brought into contact with the liner, and the liner is welded to the inner surface of the shell half over the entire area of the liner along the welding pattern.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

DESCRIPTION

MAGNETIC DISC CARTRIDGE, METHOD OF MANUFACTURING
THE SAME AND METHOD OF CLEANING LINERS OF THE SAMEField of the Invention

5 This invention relates to a magnetic disc
cartridge, and more particularly to a magnetic disc
cartridge comprising a casing formed of upper and lower
shell halves mated together, a disc-like recording medium
supported for rotation in the casing and a pair of liners
10 respectively fixed to the inner surfaces of the upper and
lower shell halves and to a method of manufacturing the
same. This invention also relates to a method of cleaning
the liners.

Background of the Invention

15 In a magnetic disc cartridge comprising a disc-like
recording medium supported for rotation in a casing formed
of upper and lower shell halves, a pair of liners formed of
nonwoven fabric or the like are generally fixed to the
inner surfaces of the upper and lower shell halves,
20 respectively.

 The liners are for protecting the recording medium
and are formed of nonwoven fabric or the like of rayon or
the like in a predetermined shape. The liners are fixed to
the inner surfaces of the upper and lower shell halves by
25 welding such as ultrasonic welding.

 Each liner is generally octagonal in contour and is

provided with a central opening and a slit-like cutaway portion which is opposed to the magnetic head insertion opening formed in the corresponding shell half.

When welding the liner to the shell half, a welding horn is pressed against the liner placed on the inner surface of the shell half and heat or ultrasonic vibration is applied to the welding horn, thereby fusing the inner surface of the shell half to the liner.

For example, there has been proposed in Japanese Patent Application No. 9(1997)-296838, a method of fixing a liner to the inner surface of a shell half by ultrasonic welding in which an energy director in the form of a protrusion is formed in a predetermined pattern on the inner surface of the shell half, the liner is placed on the energy director, and an ultrasonic welding horn is pressed against the liner so that the energy director is fused to the liner.

In the past, the liner is fixed to the shell half only at a part of its peripheral edge. Accordingly the non-fixed part of the peripheral edge and/or the central portion of the liner is in a floating condition and can be brought into contact with the recording medium. However, recently, as the recording capacity of the recording medium increases, it becomes necessary to rotate the recording medium at a higher speed. When the recording medium rotated at a high speed is constantly in contact with the

liner, contaminants can be produced, for instance, by separation of fibers from the liner. When such contaminants adhere to the recording medium and/or the magnetic head, recording and reproducing performance can be adversely affected, recording medium driving torque can be increased, and the recording medium can wobble during rotation. Accordingly, there is a tendency to reduce contact of the liner to the recording medium.

Further since the liner is stamped out from a sheet of unwoven fabric, when the liner is not welded over its entire peripheral edge, cut fibers can drop from its peripheral edge and can adhere to the surface of the recording medium to cause drop out.

Further since the liner is formed of a hygroscopic material such as rayon, when the central portion of liner is not fixed to the inner surface of the shell half, the liner is deformed in such a manner that the central portion bulges upward due to hygroscopicity under the conditions of 60° C in temperature and 90% in humidity. When the liner is thus deformed, the bulging portion is brought into contact with the recording medium which rotating at a high speed, which gives rise to the aforesaid problems.

Summary of the Invention

In view of the foregoing observations and description, the primary object of the present invention is to provide a method of manufacturing a magnetic disc

cartridge which can prevent fibers from dropping from the peripheral edges of the liners and can prevent the liners from constantly contacting with the rotating recording medium.

5 Another object of the present invention is to provide a method of manufacturing a magnetic disc cartridge which can prevent the central portions of the liners from bulging into contact with the recording medium even if they absorb moisture.

10 Still another object of the present invention is to provide a magnetic disc cartridge in which the recording medium can be effectively cleaned by the liners without substantially increasing the recording medium drive torque.

15 Still another object of the present invention is to provide a method of cleaning a liner of a magnetic disc cartridge which can effectively remove dust and free fibers from the liner without damaging the casing and/or the recording medium.

20 In accordance with a first aspect of the present invention, there is provided a method of manufacturing a magnetic disc cartridge comprising a casing formed of upper and lower shell halves mated together, a disc-like recording medium supported for rotation in the casing and an octagonal liner fixed to each of the inner surfaces of
25 the upper and lower shell halves by use of a welding horn, the liner having a substantially octagonal outer contour

defined by an outer peripheral edge, a central opening defined by an inner peripheral edge, and a slit-like cutaway portion defined by a pair of linear edges extending between the outer peripheral edge and the inner peripheral edge, which method is characterized in that

the welding horn has a welding face (the front end face) whose outer contour is an octagon conforming to the outer contour of the liner so that the liner is welded to the inner surface of the shell half substantially over the entire outer peripheral edge thereof.

It is preferred that the liner be welded to the inner surface of the shell half substantially over the entire outer peripheral edge, the inner peripheral edge and the linear edges.

The liner need not be welded to the inner surface of the shell half continuously over the edges described above but may be welded at a plurality of spots along the edges provided that the spots are sufficiently closely arranged to prevent fibers from dropping from the edges.

The liner may be welded to the inner surface of the shell half by forming an energy director protrusion on the inner surface of the shell half along the edge or edges of the liner to be welded or by forming a protrusion on the welding face of the welding horn along the edge or edges of the liner to be welded.

It is preferred that the liner be electrostatically

processed to attract and hold fiber dust.

In accordance with a second aspect of the present invention, the surface of an edge portion of the liner facing the recording medium is made more distant from the recording medium than the other part of the liner and fixing agent is caused to soak into the edge portion and is solidified there.

The surface of an edge portion of the liner facing the recording medium may be made more distant from the recording medium than the other part of the liner, for instance, by forming a recess in the inner surface of the shell half or by compressing the part of the liner with the inner surface of the shell half held flat.

The fixing agent may be adhesive applied to the liner or may be molten resin obtained by fusing the shell half by applying heat or ultrasonic vibration.

In accordance with a third aspect of the present invention, there is provided a method of manufacturing a magnetic disc cartridge comprising a casing formed of upper and lower shell halves mated together, a disc-like recording medium supported for rotation in the casing and a liner fixed to each of the inner surfaces of the upper and lower shell halves by ultrasonic welding by use of an ultrasonic welding horn, the liner having an outer contour defined by an outer peripheral edge, a central opening defined by an inner peripheral edge, and a slit-like

cutaway portion defined by a pair of linear edges extending between the outer peripheral edge and the inner peripheral edge, which method is characterized in that said ultrasonic welding horn is provided with a welding pattern in the form of a protrusion pattern formed on a welding face thereof over the entire welding area in which the ultrasonic welding horn is brought into contact with the liner, and the liner is welded to the inner surface of the shell half over the entire area of the liner along the welding pattern.

The welding pattern may be a longitudinal or transverse stripe pattern, a grid pattern, a radial pattern or the like. It is preferred that the welding pattern be uniformly spaced over the entire area of the liner opposed to the recording area of the recording medium. Further the welding pattern may be of the same form over the entire area of the liner or may be of different forms between the edge portion of the liner along the edges of the liner and the inner portion of the liner opposed to the recording area of the recording medium.

In accordance with the method of the third aspect of the present invention, the liner is welded to the inner surface of the shell half along the welding pattern over the entire area of the liner and accordingly the liner cannot largely bulge even if the liner absorbs moisture, whereby the liner is prevented from contacting the

recording medium rotating at a high speed. Accordingly,
production of contaminants and increase of the recording
medium driving torque can be suppressed, and the recording
medium can be prevented from wobbling during rotation,
5 whereby good recording and reproducing characteristics can
be ensured and the recording medium can be stably rotated
at a high speed.

In the case where the energy director in the form
of a protrusion formed on the inner surface of the shell
10 half is fused, fused components can penetrate through the
liner up to the surface thereof and can be solidified
there. When the recording medium is brought into contact
the solidified components, recording quality can be
deteriorated. To the contrast, when the ultrasonic welding
15 horn is provided with the welding pattern in the form of a
protrusion pattern and the inner surface of the shell half
is flat, fused components of the shell half less penetrates
through the liner up to the surface thereof and accordingly
even if the solidified components of the shell half is
20 brought into contact with the recording medium, the
recording quality is less affected.

In accordance with a fourth aspect of the present
invention, there is provided a magnetic disc cartridge
comprising a casing formed of upper and lower shell halves
25 mated together, a disc-like recording medium supported for
rotation in the casing and a pair of liners respectively

fixed to the inner surfaces of the upper and lower shell halves, each of the upper and lower shell halves being provided with a magnetic head insertion opening and each of the liners having a slit-like cutaway portion opposed to the magnetic head insertion opening of the corresponding shell half, wherein the improvement comprises that

a part of each of the liners extending upstream from the edge of the cutaway portion as seen in the direction of rotation of the recording medium is not fixed to the inner surface of the shell half so that the unfixed part can float from the inner surface of the shell half into contact with the surface of the recording medium.

It is preferred that at least an edge portion of the part of the unfixed part of the liner to be brought into contact with the recording medium be subjected to fiber fixing treatment for preventing hairiness and separation of fibers. Such fiber fixing treatment may involve, for instance, application of adhesive, or heat fusing. The edge portion of the part of the unfixed part of the liner may be further subjected to chemical dust treatment for enhancing dust adsorbability.

It is preferred that the unfixed part be formed within 60° from the center of the magnetic head insertion window as measured in the direction of rotation of the recording medium in view of ensuring sufficient dust wiping action without excessively increasing the recording medium

drive resistance.

When a resilient member or a rigid member is disposed between the unfixed part and the inner surface of the shell half to urge the unfixed part toward the recording medium, the unfixed part can be surely brought into contact with the surface of the recording medium and dust wiping action is enhanced. For example, the resilient member may be formed of the same material as the liner and the rigid member may be in the form of a rib formed on the inner surface of the shell half.

In accordance with a fifth aspect of the present invention, there is provided a method of cleaning a liner of a magnetic disc cartridge comprising a casing formed of upper and lower shell halves mated together, a disc-like recording medium supported for rotation in the casing and a pair of liners respectively fixed to the inner surfaces of the upper and lower shell halves, which method comprising the steps of

positioning each of the shell halves bearing thereon the liner fixed thereto with the surface of the liner opposed to a front end face of an ultrasonic welding horn at a predetermined space therefrom,

vibrating the liner by ultrasonic wave radiated from the front end face of the ultrasonic welding horn, and blowing an air flow against the surface of the liner.

It is preferred that the distance between the liner and the front end face of the ultrasonic welding horn be an integral multiple of a half wavelength of the ultrasonic wave as propagating in the air.

5 Further the ultrasonic welding horn may be moved relatively to the liner in a range including an integral multiple of a half wavelength of the ultrasonic wave as propagating in the air.

10 In accordance with a sixth aspect of the present invention, there is provided a method of cleaning a liner of a magnetic disc cartridge comprising a casing formed of upper and lower shell halves mated together, a disc-like recording medium supported for rotation in the casing and a pair of liners respectively fixed to the inner surfaces of
15 the upper and lower shell halves, which method comprising the steps of

bringing each of the shell halves bearing thereon the liner fixed thereto into contact with an ultrasonic welding horn,

20 vibrating the liner by ultrasonic wave applied to the shell half from the ultrasonic welding horn, and blowing an air flow against the surface of the liner.

25 It is preferred that the shell half be supported by an elastic means disposed on the side of the shell half remote from the ultrasonic welding horn.

The shell half may be placed on a support table supported by an air cylinder.

Brief Description of the Drawings

Figure 1 is an exploded perspective view of a magnetic disc cartridge manufactured by a method in accordance with a first embodiment of the present invention,

Figure 2 is a view showing an example of the shape of the welding face of the ultrasonic welding horn employed for carrying out the method of the first embodiment,

Figure 3 is a view showing a modification of the pattern of the energy director to be formed on the inner surface of the shell half,

Figure 4 is a view showing another example of the shape of the welding face of the ultrasonic welding horn employed for carrying out the method of the first embodiment,

Figure 5 is an exploded perspective view of a magnetic disc cartridge manufactured by a method in accordance with a second embodiment of the present invention,

Figure 6 is a view showing an example of the welding pattern to be formed on the welding face of the ultrasonic welding horn,

Figure 7 is a view showing another example of the welding pattern to be formed on the welding face of the

ultrasonic welding horn,

Figure 8 is a view showing still another example of the welding pattern to be formed on the welding face of the ultrasonic welding horn,

5 Figure 9 is a fragmentary cross-sectional view showing an important part of a magnetic disc cartridge manufactured by a method in accordance with a third embodiment of the present invention,

10 Figures 10A and 10B are views for illustrating an example of the method of bonding the liner to the shell half by use of adhesive in the third embodiment,

 Figures 11A to 11C are views for illustrating another example of the method of bonding the liner to the shell half by use of adhesive in the third embodiment,

15 Figures 12A and 12B are views for illustrating still another example of the method of bonding the liner to the shell half by use of adhesive in the third embodiment,

20 Figures 13A to 13C are views for illustrating still another example of the method of bonding the liner to the shell half by use of adhesive in the third embodiment,

 Figures 14A and 14B are views for illustrating an example of the method of bonding the liner to the shell half by welding in the third embodiment,

25 Figures 15A and 15B are views for illustrating another example of the method of bonding the liner to the shell half by welding in the third embodiment,

Figures 16A and 16B are views for illustrating examples of the protrusion pattern to be formed on the inner surface of the shell half,

Figure 17 is an exploded perspective view of a magnetic disc cartridge in accordance with a fourth embodiment of the present invention,

Figure 18 is a fragmentary cross-sectional view of the magnetic disc cartridge of the fourth embodiment,

Figure 19 is a fragmentary cross-sectional view showing a modification of the magnetic disc cartridge of the fourth embodiment,

Figure 20 is a fragmentary cross-sectional view showing another modification of the magnetic disc cartridge of the fourth embodiment,

Figure 21 is a schematic view showing a system for carrying out a method of cleaning a magnetic disc cartridge in accordance with a fifth embodiment of the present invention,

Figure 22 is a schematic view showing a system for carrying out a method of cleaning a magnetic disc cartridge in accordance with a sixth embodiment of the present invention, and

Figure 23 is a fragmentary view showing a modification of the system shown in Figure 22.

Preferred Embodiment of the Invention

In Figure 1, a magnetic disc cartridge manufactured

by a method in accordance with a first embodiment of the present invention comprises a flat casing C formed of upper and lower shell halves 1 and 2 which are formed of synthetic resin such as acrylonitrile-butadiene-styrene copolymer. A recording medium (magnetic disc) 4 with a central core member 3 mounted on the center thereof is supported for rotation in the casing C. An upper liner 5 is fixed to the inner surface of the upper shell half 1 and a lower liner 6 is fixed to the inner surface of the lower shell half 2.

The recording medium 4 comprises a flexible disc-like base formed of resin such as polyethylene terephthalate and magnetic layers formed on opposite sides of the base. Inner and outer peripheral edge portions of the recording medium 4 form a non-recording area 4b and the annular portion between the inner and outer peripheral edge portions forms a recording area 4a.

The upper and lower shell halves 1 and 2 are flat and square in shape, and are provided with outer peripheral ribs 1a and 2a which form side walls of the casing C. Inner ribs 1b and 2b are formed to extend obliquely at each corner of the upper and lower shell halves 1 and 2 and magnetic head insertion openings 10 and 11 are formed in the respective shell halves 1 and 2. A spindle hole 2c through which a spindle of a recording and reproducing system acts on the center core member 3 is formed in the

lower shell half 2 at the center thereof. Though not shown, a shutter member is mounted on the casing C to be slidable left and right to close and open the magnetic head insertion openings 10 and 11.

5 The upper and lower liners 5 and 6 are fixed by ultrasonic welding to inner surfaces of the upper and lower shell halves 1 and 2 inside the inner ribs 1b and 2b. The middle portion of each inner ribs 1b and 2b are curved to extend along the outer peripheral edge of the recording
10 medium 4.

 An annular protrusion 12 extends downward from the inner surface of the upper casing half 1 at the center thereof and is fitted in the central core member 3 on the recording medium 4, thereby limiting movement of the
15 recording medium 4 in the radial direction thereof relative to the casing C.

 The liners 5 and 6 are of the same shape and substantially octagonal in outer contour. Each liner is provided with a slit at a portion opposed to the magnetic
20 head insertion opening (10 or 11) and a central opening which is slightly larger than the annular protrusion 12 or the spindle hole 2c. Each liner is formed of, for instance, unwoven fabric such as of a blend of rayon and PET or nylon. Unwoven fabric of a blend of continuous
25 fibers of cotton cellulose (70%) and PET fibers (30%) is advantageous in that separation of fibers is less.

Each of the upper and lower shell halves 1 and 2 is provided with an energy director 14 in the form of a protrusion formed on the inner surface of the shell half in a predetermined pattern. In the example shown in Figure 1, the pattern of the energy director 14 comprises an edge portion pattern formed of a protrusion extending along the outer peripheral edge, the inner peripheral edge and the linear edges of the slit of the liner and an inside pattern formed of a plurality of radial protrusions extending from the part of the edge portion pattern extending along the inner peripheral edge defining the central opening to the part of the same extending along the outer peripheral edge.

The energy director 14 may be formed of a continuous protrusion which is triangular in cross-section or of a plurality of discontinuous protrusions. The radial protrusions in the inside pattern may be more densely formed or less densely formed though it is preferred that they are arranged at substantially regular intervals in the circumferential direction.

The liners 5 and 6 are fixed to the inner surfaces of the respective shell halves 1 and 2 by ultrasonic welding by use of an ultrasonic welding horn 20 having a welding face 20a which is octagonal in outer contour as shown in Figure 2. The welding face 20a is substantially the same as the liners 5 and 6 in shape and dimensions. That is, the welding face 20a of the ultrasonic welding

horn 20 is substantially octagonal in outer contour and is provided with a central opening corresponding to the central opening of the liner.

When welding the liner to the shell half by use of the ultrasonic welding horn 20, the shell half (1 or 2) is placed on a support table of an ultrasonic welding machine and the liner (5 or 6) is set to the inner surface of the shell half in a predetermined position. Then the welding face 20a of the ultrasonic welding horn 20 is pressed against the liner and ultrasonic vibration is applied to the ultrasonic welding horn 20, whereby the energy director 14 is fused and welded to the liner.

The pattern of the energy director 15 shown in Figure 3 comprises an edge portion pattern formed of a protrusion extending along the outer peripheral edge, the inner peripheral edge and the linear edges of the slit of the liner and an inside pattern formed of a plurality of longitudinal and transverse protrusions intersecting each other in a grid pattern.

The inside pattern may be formed of a protrusion or protrusions formed in a stripe pattern, a helical pattern, a concentric circle pattern.

It is preferred that each protrusion forming the energy director be triangular in cross-section and about 0.1mm in width of its top.

Instead of forming an energy director on the inner

surface of the shell half, a welding pattern in the form of a protrusion pattern may be formed on the welding face of the ultrasonic welding horn as shown in Figure 4.

In Figure 4, an ultrasonic welding horn 21 has a welding face 21a which is substantially equal to the liner in shape and size. The welding face 21a is provided with a welding pattern A in the form of a protrusion pattern formed along the outer peripheral edge, the inner peripheral edge and the linear edges of the slit of the liner. The welding pattern A is formed of a plurality of radial protrusions arranged at a high density (e.g., at intervals of 1mm) at the part along the outer peripheral edge of the welding face 21a, of a plurality of long and short radial protrusions which are alternately arranged at the part along the inner peripheral edge of the welding face 21a, and of a plurality of inclined protrusions arranged at a higher density at the part along the opposite edges of the slit. It is preferred that each protrusion forming the welding pattern be triangular in cross-section and about 0.1mm in width of its top.

Each of the four sides of the octagonal welding face 21a corresponding to the four sides of the liner which are opposed to the four corners of the shell half is arcuately bulges outward beyond the outer peripheral edge of the liner. In Figure 4, inner line a of the welding pattern A corresponds to the outer peripheral edge of the

recording area 4a of the recording medium 4, inclined
linear lines b correspond to the outer peripheral edge of
the liner and outer arcuate lines c of the bulging portion
correspond to the outer peripheral edge of the recording
medium 4.

The ultrasonic welding horn 21 is for welding the
liner to the inner surface of the shell half at the portion
outside the recording area 4a. But for the bulging portion
indicated at c, the width of the welding pattern becomes
too small at the middle of the inclined sides opposed to
the corners of the shell half. Accordingly, by increasing
the width of the welding pattern there within a range in
which the welding face of the ultrasonic welding horn does
not interfere with the inner ribs 1b and 2b of the shell
halves 1 and 2, production of the welding pattern is
facilitated.

Though, in the embodiment described above, the
liner is welded by ultrasonic welding, it may be welded by
heat-welding. Further when the liner is electrostatically
processed, the liner can attract dust and prevent dust from
adhering to the recording medium 4.

A magnetic disc cartridge manufactured by a method
in accordance with a second embodiment of the present
invention will be described with reference to Figures 5 to
8, hereinbelow.

Figure 5 shows a magnetic disc cartridge C

manufactured by a method in accordance with the second embodiment of the present invention. The magnetic disc cartridge shown in Figure 5 is substantially the same as that shown in Figure 1 except that the inner surfaces of the upper and lower shell halves are not provided with an energy director and are substantially flat at the part where the liners are fixed. Accordingly, the elements analogous to those shown in Figure 1 are given the same reference numerals and will not be described here.

As shown in Figure 5, the inner surfaces of the shell halves 1 and 2 are substantially flat inside the inner ribs 1b and 2b.

The liners 5 and 6 are fixed to the inner surfaces of the respective shell halves 1 and 2 by ultrasonic welding by use of an ultrasonic welding horn 120 (Figure 6). As shown in Figure 6, the ultrasonic welding horn 120 has an octagonal welding face 120a which is substantially the same as the liners 5 and 6 in shape and dimensions. The welding face 120a of the ultrasonic welding horn 120 is provided with a central opening corresponding to the central opening of the liner and a slit corresponding to the slit of the liner. A welding pattern in the form of a protrusion pattern is formed over the entire area of the welding face 120a of the ultrasonic welding horn 120.

Each of the four sides of the octagonal welding face 120a corresponding to the four sides of the liner

which are opposed to the four corners of the shell half is arcuately bulges outward beyond the outer peripheral edge of the liner. The radius of curvature of the bulging portion is substantially equal to that of the outer peripheral edge of the recording medium 4.

The example of the welding pattern shown in Figure 6 comprises an edge portion pattern 121 and an inner side pattern 122. The edge portion pattern 121 is formed along the outer peripheral edge, the inner peripheral edge of the welding face 120a and along the opposite edges of the slit of the same (121a). The edge portion pattern 121 is formed of a plurality of radial protrusions arranged at a high density at the part along the outer peripheral edge of the welding face 120a, of a plurality of long and short radial protrusions which are alternately arranged at the part along the inner peripheral edge of the welding face 120a, and of a plurality of inclined protrusions arranged at a higher density at the part 121a along the opposite edges of the slit. The inner side pattern 122 is formed of a plurality of longitudinal protrusions and transverse protrusions which intersect each other to form a grid pattern. Each of the longitudinal and transverse protrusions may be discontinuous.

In Figure 6 (and also in Figures 7 and 8), the lines but those representing the contour of the welding face 120a of the ultrasonic welding horn 120 and the

boundary between the edge portion pattern 121 and the inner side pattern 122 (a thin groove) show the top (welding line) of the protrusions forming the welding pattern. The welding lines are formed at pitches of 1 to 2mm.

5 When welding the liner to the shell half by use of the ultrasonic welding horn 120, the shell half (1 or 2) is placed on a support table of an ultrasonic welding machine and the liner (5 or 6) is set to the inner surface of the shell half in a predetermined position. Then the welding
10 face 120a of the ultrasonic welding horn 120 is pressed against the liner and ultrasonic vibration is applied to the ultrasonic welding horn 120, whereby the portion of the inner surface of the shell half opposed to the welding pattern is fused and welded to the liner.

15 The welding pattern shown in Figure 7 differs from that shown in Figure 6 in that the inner side pattern 123 is a longitudinal stripe pattern formed of a plurality of parallel longitudinal protrusions (each of which may be of either a continuous protrusion or a plurality of
20 discontinuous protrusions). The stripe pattern may be formed of a plurality of transverse or inclined protrusions.

25 The welding pattern shown in Figure 8 differs from that shown in Figure 6 in that the inner side pattern 124 is formed of a plurality of short protrusions which extend in radial directions and are arranged in a plurality of

concentric circles. The short protrusions are formed at substantially the same pitches in all the concentric circles. In Figure 8, the concentric lines in the inner side pattern 124 represent thin grooves and the radial lines represent the protrusions.

Though, in the examples shown in Figures 6 to 8, the edge portion pattern 121 is different in form from the inner side pattern 122, 123 or 124, the welding pattern may be the same over the entire area and may be a stripe pattern, a grid pattern, a radial pattern or the like.

In the method of welding the liners 5 and 6 to the upper and lower shell halves 1 and 2, since each liner is welded to the inner surface of the corresponding shell half along the welding pattern over the entire area of the liner, the liner cannot largely bulge even if the liner absorbs moisture, whereby the liner is prevented from contacting the rotating recording medium 4. Accordingly, production of liner dust and increase of the recording medium driving torque can be suppressed.

A method of manufacturing a magnetic disc cartridge in accordance with a third embodiment of the present invention will be described with reference to Figures 9 to 16B, hereinbelow.

In this embodiment, the surface of the outer peripheral edge portion of each of the liners facing the recording medium 4 is made more distant from the recording

medium 4 than the other part of the liner and fixing agent is caused to soak into the edge portion and is solidified there. Since the upper and lower liners 5 and 6 are fixed to the upper and lower shell halves 1 and 2 in the same manner, only the upper liner 5 will be described hereinbelow. As shown in Figure 9, the upper wall portion 1d of the shell half 1 is provided with an annular recess 1e in its inner surface at a portion opposed to the outer peripheral edge portion 5a of the liner 5 and the outer peripheral edge portion 5a of the liner 5 is fixed to the bottom of the recess 1e so that the surface of the peripheral edge portion 5a facing the recording medium 4 is positioned more distant from the recording medium 4 than the other part of the liner 5. Further fixing agent S is caused to soak into the peripheral edge portion 5a and is solidified there.

The difference h in level or distance from the recording medium 4 between the peripheral edge portion 5a and the other portion of the liner 5 is set to be 0.05 to 0.3mm. The level difference h may be made in various manners other than by forming a recess in the inner surface of the shell 1 as shown in Figure 9. For example, the level difference h may be made by compressing the outer peripheral edge portion of the liner 5 with the inner surface of the shell half 5 held flat.

The fixing agent S may be adhesive applied to the

liner or may be molten resin obtained by fusing the shell half by applying heat or ultrasonic vibration as will be described later.

For example, when the fixing agent S is adhesive,
5 an adhesive layer (e.g., ultraviolet-setting adhesive) 7 is formed on the bottom of the recess 1e and the liner 5 is placed on the inner surface of the shell half 1 as shown in Figure 10A. Then the outer peripheral edge portion 5a of the liner 5 is pressed against the adhesive layer 7,
10 thereby deforming the liner 5 along the recess 1e and causing the adhesive 7 to soak into the peripheral edge portion 5a up to the surface facing the recording medium 4 as shown in Figure 10B. Then the adhesive 7 is solidified by exposing to ultraviolet rays.

15 In the example shown in Figures 10A and 10B, the liner 5 is bonded to the shell half 1 only at its outer peripheral portion 5a. However the liner 5 may be bonded to the shell half 1 over the entire area thereof. In this case, in order to cause the adhesive to soak into the outer
20 peripheral edge portion 5a, the amount of adhesive applied to the outer peripheral edge portion 5a is increased.

For example, an adhesive layer 7 is formed on the bottom of the recess 1e in a predetermined thickness as shown in Figure 11A, and then another adhesive layer 7 is
25 formed on the inner surface of the shell half 1 uniformly over the entire area of the liner 5 so that the thickness

of the adhesive layer 7 becomes larger at the part opposed to the outer peripheral edge portion 5a of the liner 5 than the other part as shown in Figure 11B. Then the outer peripheral edge portion 5a of the liner 5 is pressed against the adhesive layer 7, thereby deforming the liner 5 along the recess 1e and causing the adhesive 7 to soak into the peripheral edge portion 5a up to the surface facing the recording medium 4 as shown in Figure 11C. Then the adhesive 7 is solidified by exposing to ultraviolet rays.

Otherwise, an adhesive layer 7 may be formed at one time on the inner surface of the shell half 1 over the entire area of the liner 5 so that the thickness of the adhesive layer 7 becomes larger at the part opposed to the outer peripheral edge portion 5a of the liner 5 than the other part as shown in Figure 12A and 12B.

Otherwise, an adhesive layer 7 is formed on the inner surface of the shell half 1 uniformly over the entire area of the liner 5 as shown in Figure 13A, and then the outer peripheral edge portion 5a of the liner 5 is pressed against the adhesive layer 7 so that the liner 5 is deformed along the recess 1e and another adhesive layer 7 is formed on the outer peripheral edge portion 5a of the liner as shown in Figure 13B. Then the adhesive layer 7 is caused to soak into the outer peripheral edge portion 5a of the liner as shown in Figure 13C.

When molten resin obtained by fusing the shell half

of ABS resin is used as the fixing agent S, the liner 5 is placed on the inner surface of the shell half 1 and a heater head (or an ultrasonic welding horn) 25 is pressed against the outer peripheral edge portion 5a of the liner 5 as shown in Figure 14A, thereby fusing the inner surface of the shell half 1 so that molten resin is caused to soak into the outer peripheral edge portion 5a. After the molten resin is solidified, the outer peripheral edge portion 5a of the liner 5 is partly embedded in the inner surface of the shell half 1 as shown in Figure 14B.

When molten resin obtained by fusing the shell half is used as the fixing agent S, a protrusion pattern 8 like an energy director which is used in ultrasonic welding may be formed on the bottom of the recess 1e as shown in Figure 15A. In this case, the protrusion pattern 8 is fused and the molten resin of the protrusion pattern 8 is caused to soak into the outer peripheral edge portion 5a of the liner 5 as shown in Figure 15B.

The protrusion pattern 8 may comprise, for instance, a plurality of stripes as shown in Figure 16A or a plurality of zigzag protrusions intersecting each other as shown in Figure 16B.

In the magnetic disc cartridge manufactured by the method of this embodiment, since the outer peripheral edge portion 5a of the liner 5 is more distant from the recording medium 4 than the other part, the outer

peripheral edge portion 5a from which fibers are apt to be separated is less apt to be brought into contact with the rotating recording medium 4, whereby fraying of the liner 5 is suppressed and separation of fibers is suppressed.

5 Further by virtue of the fixing agent S, liner dust or the like on the surface of the liner can be prevented from leaving the outer peripheral edge portion 5a of the liner 5.

10 A magnetic disc cartridge in accordance with a fourth embodiment of the present invention will be described with reference to Figures 17 to 20, hereinbelow.

The magnetic disc cartridge of this embodiment is substantially the same as that shown in Figure 1 and accordingly, the elements analogous to those shown in
15 Figure 1 are given the same reference numerals and will not be described here. The magnetic disc cartridge of this embodiment mainly differs from that shown in Figure 1 in that a part of the liners 5 and 6 which is positioned upstream of the magnetic head insertion openings 10 and 11
20 as seen in the direction D of rotation of the recording medium 4 is not fixed to the inner surface of the shell half. That is, the liner 5 is not welded to the inner surface of the upper shell half 1 at a part 5A upstream of the magnetic head insertion opening 10 as seen in the
25 direction D of rotation of the recording medium 4, and is welded to the inner surface of the upper shell half 1 over

the entire area of the other part 5B along welding lines. Similarly the liner 6 is not welded to the inner surface of the lower shell half 2 at a part 6A upstream of the magnetic head insertion opening 11 as seen in the direction D of rotation of the recording medium 4, and is welded to the inner surface of the lower shell half 2 over the entire area of the other part 6B along a welding pattern.

The welding pattern is formed of short welding lines which are closely spaced from each other at a part along the outer and inner peripheral edges and an edge of the slit of the liner and is formed of a plurality of stripe-like welding lines at the inner part of the liner.

As shown in Figure 18, when the recording medium 4 is rotated at a high speed, the free ends of the non-welded parts 5A and 6A of the liners 5 and 6 near the magnetic head insertion openings 10 and 11 are attracted toward the recording medium 4 by an air flow generated by rotation of the recording medium 4 and brought into contact with the surface of the recording medium 4 under a light pressure.

The edge portions 5C and 6C of the non-welded parts 5A and 6A are subjected to fiber fixing treatment in order to prevent hairiness and separation of fibers. Such fiber fixing treatment may involve, for instance, application and drying of adhesive, or application of heat to hot melt fibers. The portions may be further subjected to chemical dust treatment for enhancing dust adsorbability.

The fiber fixing treatment is carried out at least on the edge portions of the parts of the non-welded parts 5A and 6A which are brought into contact with the recording medium 4 and need not be carried out on the parts which are not brought into contact with the recording medium 4. Of course, the fiber fixing treatment may be carried out over the entire edge portions of the liners 5 and 6.

It is preferred that the non-welded parts 5A and 6A are equal to each other in shape and size so that the recording medium 4 can be stably rotated without wobbling or the like. Further the non-welded parts 5A and 6A are formed so that they are brought into contact with the surface of the rotating recording medium 4 under a light pressure.

Specifically, it is preferred that the non-welded parts 5A and 6A be formed within 60° from the center of the magnetic head insertion windows 10 and 11 as measured in the direction D of rotation of the recording medium 4 ($\alpha \leq 60^\circ$) in view of ensuring sufficient dust wiping action without excessively increasing the recording medium drive resistance.

Since the non-welded parts 5A and 6A are provided upstream of the magnetic head insertion openings 10 and 11 and part of the recording medium 4 which is about to be brought into contact with the magnetic head is wiped, generation of drop-out can be effectively prevented.

Further since the liners 5 and 6 are brought into contact with the recording medium 4 only locally and at the same time they are brought into contact with the recording medium 4 by floating action of the free-end portions of the non-welded parts 5A and 6A, contact of the liners 5 and 6 with the recording medium 4 hardly causes loss of recording medium drive torque and accordingly the recording medium 4 can be stably rotated at a high speed by a small drive motor.

Figures 19 and 20 show a pair of modifications of the magnetic disc cartridge of this embodiment. In the modification shown in Figure 19, resilient members 7, which are of, for instance, the same material as the liners 5 and 6, are positioned between the non-welded parts 5A and 6A and the inner surfaces of the upper and lower shell halves 1 and 2. The resilient members 7 promote the floating action of the non-welded parts 5A and 6A in response to rotation of the recording medium 4.

In the modification shown in Figure 20, ribs 1D and 2D are formed on the inner surface of the upper and lower shell halves 1 and 2. The ribs 1D and 2D also promote the floating action of the non-welded parts 5A and 6A in response to rotation of the recording medium 4.

A method of cleaning the liners 5 and 6 in accordance with a fifth embodiment of the present invention will be described with reference to Figure 21. Figure 21

shows an example of a liner cleaning system for carrying out the method of the fifth embodiment of the present invention.

The liner cleaning system 220 shown in Figure 21 is for cleaning the liner 5 (or 6) after it is fixed to the shell half 1 (or 2) and before the shell halves 1 and 2 are assembled into a magnetic disc cartridge. The liner cleaning system 220 comprises a shell half support table 221 on which the shell half 1 with the liner 5 is placed. An ultrasonic welding horn 223 connected to an ultrasonic wave generator 222 is disposed above the shell half support table 221 with its front end face 223a directed downward. The front end face 223a of the ultrasonic welding horn 223 is opposed to the surface of the liner 5 at a predetermined distance d therefrom. An air blow nozzle 225 which blows an air flow against the surface of the liner 5 is disposed on one side of the ultrasonic welding horn 223 and a suction duct 226 which sucks dust blown away the surface of the liner 5 is disposed on the other side of the ultrasonic welding horn 223.

Ultrasonic wave vibration generated by the ultrasonic wave generator 222 is applied to the liner 5 from the front end face 223a of the ultrasonic welding horn 223 and at the same time an air flow is blown against the surface of the liner 5 while the suction duct 226 sucks air. With this arrangement, fiber fractions, dust and the

like trapped in the liner 5 are released from the liner 5 by vibration of the liner 5, blown away the liner 5 by the air flow and sucked into the suction duct 226, whereby the liner 5 is removed with fiber fractions, dust and the like.

5 It is preferred that the ultrasonic wave vibration be not higher than 50kHz in frequency. More preferably the frequency is in the range of 15 to 25kHz. The distance d between the front end face 223a of the ultrasonic welding horn 223 and the liner 5 is set to an integral multiple of
10 a half wavelength of the ultrasonic wave as propagating in the air. For example, when the frequency of the ultrasonic wave is 20kHz, the half wavelength is $\{340[\text{m/s}]/20[\text{kHz}]\} \times 1/2 = 8.5\text{mm}$ since the speed of sound in the air at normal temperatures is about 340m/s. Accordingly, the distance d
15 between the front end face 223a of the ultrasonic welding horn 223 and the liner 5 is preferably 8mm to 9mm.

 As the frequency of the ultrasonic wave becomes higher, the distance d becomes too short when it is set to a half of the wavelength. Accordingly when the frequency
20 is 40kHz, the distance d is set to be equal to the wavelength, i.e., 8mm to 9mm. However, since as the distance d increases, attenuation becomes larger, it is preferred that the distance d be set to a half of the wavelength.

25 The amplitude of the front end face 223a of the ultrasonic welding horn 223 should be about 1 to 40 μm (half

amplitude) and is preferably 10 to 20 μ m in the case where the frequency is 20kHz. When the amplitude is too large, the liner 5 generates heat and the shell half 1 can be damaged, e.g., deformed or fused, and at the same time, manufacture of the ultrasonic wave generator 222 and/or the ultrasonic welding horn 223 becomes difficult.

The ultrasonic welding horn 223 may be moved back and forth relatively to the liner 5 in a range including an integral multiple of a half wavelength of the ultrasonic wave as propagating in the air. When the distance d is changed while the ultrasonic wave vibration is being applied to the liner 5, vibration of dust in the liner 5 is changed and cleaning action is enhanced. The amount of movement of the ultrasonic welding horn 223 is preferably 0.5 to 2mm in the case where the frequency is 20kHz. Generally, the amount of movement of the ultrasonic welding horn 223 is set larger as the frequency becomes lower.

Preferably the ultrasonic wave vibration is applied to the liner 5 for 0.1 to 2 seconds. When the ultrasonic wave vibration is applied to the liner 5 for an excessively long time, the liner 5 generates heat and the shell half 1 can be damaged. Further application of ultrasonic wave of a small amplitude for a long time produced less cleaning action and a best result was obtained by application of ultrasonic wave of an amplitude of 20 μ m for 0.5 to 1.5 seconds.

It is preferred that the air blow nozzle 225 be arranged to blow pressurized air obliquely to the liner 5 over a wide area and the suction duct 226 be arranged to suck air over a wide area. When the air blow nozzle 225 is arranged to blow ionized air, static electricity generated by the ultrasonic wave vibration can be eliminated and the cleaning action is enhanced. Further though it is preferred that the air blow nozzle 25 blows air wide over the entire area of the liner 5, it is possible to move a point type nozzle to cause air flow to scan the surface of the liner 5. Further when the air flow is turned on and off at short intervals in a pulse-like fashion, cleaning action can be enhanced.

Though, in the system shown in Figure 21, the shell half 1 is directed upward with the ultrasonic welding horn 223 directed downward, it is possible to direct downward the shell half 1 with the ultrasonic welding horn 223 directed upward. In this case, dust released from the liner 5 drops away from the liner 5, which is advantageous in effectively removing the dust.

After the liner is cleaned in the manner described above, the upper and lower shell halves 1 and 2 are mated together with the recording medium 4 placed therein and bonded together by ultrasonic welding, whereby a magnetic disc cartridge is assembled.

A method of cleaning the liners 5 and 6 in

accordance with a sixth embodiment of the present invention will be described with reference to Figure 22. Figure 22 shows an example of a liner cleaning system for carrying out the method of the sixth embodiment of the present invention.

The liner cleaning system 320 shown in Figure 22 is for cleaning the liner 5 (or 6) after it is fixed to the shell half 1 (or 2) and before the shell halves 1 and 2 are assembled into a magnetic disc cartridge. The liner cleaning system 320 comprises a pressure receiving means 321 on which the shell half 1 with the liner 5 is placed with the liner 5 facing downward. An ultrasonic welding horn 323 connected to an ultrasonic wave generator 322 is disposed above the pressure receiving means 321 with its front end face 323a directed downward. The front end face 323a of the ultrasonic welding horn 323 is pressed against the outer surface of the shell half 1.

The pressure receiving means 321 comprises a support frame 324 and an elastic means 325 for supporting the shell half 1 in contact therewith is mounted on the support frame 324. The support frame 324 is supported on a pair of air cylinders 326. The elastic means 325 is formed of an elastic material such as rubber, resin or the like and comprises, for instance, four blocks each supporting one of the four corners of the shell half 1, thereby supporting the shell half 1 with the lower end of the outer

ribs 1a spaced from the upper surface of the support frame 324.

An air blow nozzle 327 which blows an air flow against the surface of the liner 5 is disposed on one side of the support frame 324 and a suction duct 328 which sucks dust blown away the surface of the liner 5 is disposed on the other side of the support frame 324.

Ultrasonic wave vibration generated by the ultrasonic wave generator 322 is applied to the shell half 1 from the front end face 323a of the ultrasonic welding horn 323 and at the same time an air flow is blown against the surface of the liner 5 while the suction duct 328 sucks air. With this arrangement, fiber fractions, dust and the like trapped in the liner 5 are released from the liner 5 by vibration of the liner 5, blown away the liner 5 by the air flow and sucked into the suction duct 328, whereby the liner 5 is removed with fiber fractions, dust and the like.

It is preferred that the ultrasonic wave vibration be not higher than 50kHz in frequency. More preferably the frequency is in the range of 15 to 25kHz. The amplitude of the front end face 323a of the ultrasonic welding horn 323 should be about 1 to 40 μ m (half amplitude) and is preferably 10 to 20 μ m in the case where the frequency is 20kHz. When the amplitude is too large, the shell half 1 generates heat and the shell half 1 can be damaged, e.g., deformed or fused, and at the same time, manufacture of the

ultrasonic wave generator 322 and/or the ultrasonic welding horn 323 becomes difficult.

Preferably the ultrasonic wave vibration is applied to the shell half 1 for 0.1 to 2 seconds. When the ultrasonic wave vibration is applied to the shell half 1 for an excessively long time, the shell half 1 generates heat and the shell half 1 can be damaged. Further application of ultrasonic wave of a small amplitude for a long time produced less cleaning action and a best result was obtained by application of ultrasonic wave of an amplitude of $20\mu\text{m}$ for 0.5 to 1.5 seconds.

It is preferred that the front end face 323a of the ultrasonic welding horn 323 be pressed against the shell half 1 at a pressure of 10 to 100gf. When this pressure is excessively high, the contact surface of the shell half 1 with the ultrasonic welding horn 323 or the elastic means 325 can generate heat and can be fused and/or dust is generated.

The elastic means 325 is for suppressing damage on the shell half 1 due to the ultrasonic vibration and is preferably formed of rubber, resin or the like such as those of silicone series or fluorine series which are excellent in heat resistance and durability. It is most preferred that the elastic member 325 be formed of high-expanded silicone rubber. Further since a cut surface of an expanded body is small in cross-sectional area or

carrying area, it is preferred that the face of the elastic means 325 in contact with the shell half 1 is a non-cut surface (molded surface). The elastic means 325 may be formed of also a silicone rubber tube inflated at a
5 suitable air pressure in a suitable thickness.

The resilient means 325 should support the shell half 1 so that the surface of the liner 5 is kept open and an air flow between the air blow nozzle 327 and the suction duct 328 is ensured. For this purpose, it is preferred
10 that the elastic means 325 be arranged to support the lower end face of the outer rib 1a of the shell half 1 at a plurality of points such as the four corners and/or some intermediates points or continuously along the sides other than the sides opposed to the air blow nozzle 327 and the
15 suction duct 328.

The air cylinders 326 expands and contracts according to the pressure from the front end face 323a of the ultrasonic welding horn 323 to hold constant the pressure acting on the shell half 1, thereby protecting the
20 shell half 1 from being damaged and ensuring stable vibration of the liner 5.

It is preferred that the air blow nozzle 327 be arranged to blow pressurized air to the liner 5 over a wide area and the suction duct 328 be arranged to suck air over
25 a wide area. When the air blow nozzle 327 is arranged to blow ionized air, static electricity generated by the

ultrasonic wave vibration can be eliminated and the cleaning action is enhanced. Further though it is preferred that the air blow nozzle 327 blows air wide over the entire area of the liner 5, it is possible to move a point type nozzle to cause air flow to scan the surface of the liner 5. Further when the air flow is turned on and off at short intervals in a pulse-like fashion, cleaning action can be enhanced.

Though, in the system shown in Figure 22, the shell half 1 is directed downward with the ultrasonic welding horn 223 directed downward, it is possible to direct upward the shell half 1 with the ultrasonic welding horn 223 directed upward.

Figure 23 shows a modification of the cleaning system shown in Figure 22. In this modification, the ultrasonic welding horn 323 is pressed against the shell half 1 only at column-like projections 232b. The projections 323b may be formed, for instance, to press the shell half 1 and apply vibration to the shell half 1 only at the four corners where the elastic means 325 supports the shell half 1. That is, the projections 323b may be formed to press the shell half 1 in positions where the shell half 1 is less apt to be deformed by application of ultrasonic vibration, e.g., positions along the outer periphery of the shell half 1 or positions where the elastic means 325 supports the shell half 1. The position

of the projections 323b may be changed according to the form of the elastic means 325.

CLAIMS

1. A method of manufacturing a magnetic disc cartridge comprising a casing formed of upper and lower shell halves mated together, a disc-like recording medium supported for rotation in the casing and a liner fixed to each of the inner surfaces of the upper and lower shell halves by ultrasonic welding by use of an ultrasonic welding horn, the liner having an outer contour defined by an outer peripheral edge, a central opening defined by an inner peripheral edge, and a slit-like cutaway portion defined by a pair of linear edges extending between the outer peripheral edge and the inner peripheral edge, which method is characterized in that

said ultrasonic welding horn is provided with a welding pattern in the form of a protrusion pattern formed on a welding face thereof over the entire welding area in which the ultrasonic welding horn is brought into contact with the liner, and the liner is welded to the inner surface of the shell half over the entire area of the liner along the welding pattern.

2. A method as defined in Claim 1 in which said welding pattern is selected from a group consisting of a longitudinal stripe pattern, a transverse stripe pattern, a grid pattern and a radial pattern.

3. A method as defined in Claim 1 in which the welding pattern is uniformly spaced over the entire area of

the liner opposed to the recording area of the recording medium.

4. A method as defined in Claim 1 in which the welding pattern is formed of a continuous protrusion.

5 5. A method as defined in Claim 1 in which the welding pattern is formed of a plurality of discontinuous protrusions.

6. A method of manufacturing a magnetic disc cartridge comprising a casing formed of upper and lower
10 shell halves mated together, a disc-like recording medium supported for rotation in the casing and an octagonal liner fixed to each of the inner surfaces of the upper and lower shell halves by use of a welding horn, the liner having a substantially octagonal outer contour defined by an outer
15 peripheral edge, a central opening defined by an inner peripheral edge, and a slit-like cutaway portion defined by a pair of linear edges extending between the outer peripheral edge and the inner peripheral edge, which method is characterized in that

20 the welding horn has a welding face whose outer contour is an octagon conforming to the outer contour of the liner so that the liner is welded to the inner surface of the shell half substantially over the entire outer peripheral edge thereof.

25 7. A method as defined in Claim 6 in which the liner is welded to the inner surface of the shell half

substantially over the entire outer peripheral edge, the inner peripheral edge and the linear edges in such a manner that the liner is welded to the inner surface of the shell half continuously over the edges or is welded at a plurality of spots arranged along the edges sufficiently closely to prevent fibers of the liner from dropping from the edges.

8. A method as defined in Claim 6 in which the liner is welded to the inner surface of the shell half by forming an energy director protrusion on the inner surface of the shell half along the edge of the liner to be welded.

9. A method as defined in Claim 6 in which the liner is welded to the inner surface of the shell half by forming a protrusion on the welding face of the welding horn along the edge of the liner to be welded.

10. A method as defined in Claim 9 in which the welding face of the ultrasonic welding horn is bulged outward where the part of the liner positioned outside the recording area of the recording medium is narrowed.

11. A method of manufacturing a magnetic disc cartridge comprising a casing formed of upper and lower shell halves mated together, a disc-like recording medium supported for rotation in the casing and a liner fixed to each of the inner surfaces of the upper and lower shell halves, which method is characterized in that

the surface of an edge portion of the liner facing

the recording medium is made more distant from the recording medium than the other part of the liner and fixing agent is caused to soak into the edge portion and is solidified there.

5 12. A method as defined in Claim 11 in which the surface of an edge portion of the liner facing the recording medium is made more distant from the recording medium than the other part of the liner by forming a recess in the inner surface of the shell half.

10 13. A method as defined in Claim 11 in which the fixing agent is adhesive.

 14. A method as defined in Claim 11 in which the fixing agent is molten resin obtained by fusing a part of the shell half.

15 15. A magnetic disc cartridge comprising
 a casing formed of upper and lower shell halves
mated together,
 a disc-like recording medium supported for rotation
in the casing, and

20 a pair of liners respectively fixed to the inner
surfaces of the upper and lower shell halves,
 each of the upper and lower shell halves being
provided with a magnetic head insertion opening and each of
the liners having a slit-like cutaway portion opposed to
25 the magnetic head insertion opening of the corresponding
shell half, wherein the improvement comprises that

a part of each of the liners extending upstream from the edge of the cutaway portion as seen in the direction of rotation of the recording medium is not fixed to the inner surface of the shell half so that the unfixed part can float from the inner surface of the shell half into contact with the surface of the recording medium.

16. A magnetic disc cartridge as defined in Claim 15 in which at least an edge portion of the part of the unfixed part of the liner to be brought into contact with the recording medium is subjected to fiber fixing treatment for preventing hairiness and separation of fibers.

17. A magnetic disc cartridge as defined in Claim 15 in which the unfixed part is formed within 60° from the center of the magnetic head insertion window as measured in the direction of rotation of the recording medium.

18. A magnetic disc cartridge as defined in Claim 15 further comprising a resilient member or a rigid member disposed between the unfixed part and the inner surface of the shell half to urge the unfixed part toward the recording medium.

19. A method of cleaning a liner of a magnetic disc cartridge comprising a casing formed of upper and lower shell halves mated together, a disc-like recording medium supported for rotation in the casing and a pair of liners respectively fixed to the inner surfaces of the upper and lower shell halves, which method comprising the

steps of

positioning each of the shell halves bearing thereon the liner fixed thereto with the surface of the liner opposed to a front end face of an ultrasonic welding horn at a predetermined space therefrom,

vibrating the liner by ultrasonic wave radiated from the front end face of the ultrasonic welding horn, and blowing an air flow against the surface of the liner.

20. A method of cleaning a liner as defined in Claim 19 in which the distance between the liner and the front end face of the ultrasonic welding horn is an integral multiple of a half wavelength of the ultrasonic wave as propagating in the air.

21. A method of cleaning a liner as defined in Claim 19 in which the ultrasonic welding horn is moved relatively to the liner in a range including an integral multiple of a half wavelength of the ultrasonic wave as propagating in the air.

22. A method of cleaning a liner of a magnetic disc cartridge comprising a casing formed of upper and lower shell halves mated together, a disc-like recording medium supported for rotation in the casing and a pair of liners respectively fixed to the inner surfaces of the upper and lower shell halves, which method comprising the steps of

bringing each of the shell halves bearing thereon
the liner fixed thereto into contact with an ultrasonic
welding horn,

vibrating the liner by ultrasonic wave applied to
the shell half from the ultrasonic welding horn, and

blowing an air flow against the surface of the
liner.

23. A method as defined in Claim 22 in which the
shell half is supported by an elastic means disposed on the
side of the shell half remote from the ultrasonic welding
horn.

24. A method as defined in Claim 22 in which the
shell half is placed on a support table supported by an air
cylinder.

INTERNATIONAL SEARCH REPORT

International Application No
PCT/JP 99/03247

A. CLASSIFICATION OF SUBJECT MATTER

IPC 6 G11B23/03 G11B23/033 G11B23/50

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 G11B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	PATENT ABSTRACTS OF JAPAN vol. 096, no. 012, 26 December 1996 (1996-12-26) -& JP 08 203234 A (FUJI PHOTO FILM CO LTD), 9 August 1996 (1996-08-09)	1-5
A	abstract; figures ---	6-10
X	EP 0 309 727 A (POLAROID CORP) 5 April 1989 (1989-04-05)	1
A	column 11, line 33 -column 13, line 36; figures ---	2-10
X	EP 0 308 161 A (HITACHI MAXELL) 22 March 1989 (1989-03-22)	1, 15-18
A	column 6, line 23 -column 8, line 10; figures 1, 2, 8 ---	2-10
	-/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- "S" document member of the same patent family

Date of the actual completion of the international search

23 September 1999

Date of mailing of the international search report

30/09/1999

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Declat, M

INTERNATIONAL SEARCH REPORT

International Application No

PCT/JP 99/03247

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 115 961 A (NAKAJIMA SABURO) 26 May 1992 (1992-05-26) column 1, line 51 -column 2, line 9	19-24
A	column 3, line 41 -column 5, line 46; figures ---	1,6,15
X	PATENT ABSTRACTS OF JAPAN vol. 096, no. 002, 29 February 1996 (1996-02-29) -& JP 07 272437 A (KAO CORP), 20 October 1995 (1995-10-20) abstract; figures ---	19,22
X	US 5 705 004 A (WATANABE SEIICHI) 6 January 1998 (1998-01-06) column 2, line 66 -column 4, line 61; figures ---	1,11
A	US 5 687 048 A (MIZUTA AKIRA) 11 November 1997 (1997-11-11) column 4, line 35 -column 5, line 67; figures ---	1-9
A	DE 39 41 334 A (FUJI PHOTO FILM CO LTD) 21 June 1990 (1990-06-21) column 5, line 46 -column 6, line 45; figures ---	1,6
A	US 4 814 927 A (IWAMOTO SHOJI ET AL) 21 March 1989 (1989-03-21) abstract; figures ---	1,6
A	US 4 773 293 A (MIZUTA AKIRA ET AL) 27 September 1988 (1988-09-27) abstract; figures -----	1,6

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/JP 99/03247

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
JP 08203234 A	09-08-1996	NONE	
EP 0309727 A	05-04-1989	US 4814926 A AT 73956 T AU 2281588 A CA 1312949 A CN 1032463 A,B DE 3869305 A DK 536988 A GR 89300108 T JP 1125778 A KR 131770 B PT 88382 A	21-03-1989 15-04-1992 06-04-1989 19-01-1993 19-04-1989 23-04-1992 29-03-1989 19-01-1990 18-05-1989 15-04-1998 31-07-1989
EP 0308161 A	22-03-1989	JP 1072375 A DE 3885829 D DE 3885829 T US 5006948 A	17-03-1989 05-01-1994 01-06-1994 09-04-1991
US 5115961 A	26-05-1992	JP 2592347 B JP 4098669 A DE 4126904 A	19-03-1997 31-03-1992 20-02-1992
JP 07272437 A	20-10-1995	NONE	
US 5705004 A	06-01-1998	JP 8221943 A	30-08-1996
US 5687048 A	11-11-1997	JP 8221930 A	30-08-1996
DE 3941334 A	21-06-1990	JP 2167636 A JP 2542249 B US 5012569 A	28-06-1990 09-10-1996 07-05-1991
US 4814927 A	21-03-1989	NONE	
US 4773293 A	27-09-1988	JP 1872632 C JP 5083358 B JP 62152696 A	26-09-1994 25-11-1993 07-07-1987

PCT COOPERATION TREATY

PCT

NOTIFICATION OF ELECTION

(PCT Rule 61.2)

From the INTERNATIONAL BUREAU

To:

Assistant Commissioner for Patents
 United States Patent and Trademark
 Office
 Box PCT
 Washington, D.C. 20231
 ÉTATS-UNIS D'AMÉRIQUE

in its capacity as elected Office

Date of mailing (day/month/year) 28 February 2000 (28.02.00)	
International application No. PCT/JP99/03247	Applicant's or agent's file reference PA3934PCT
International filing date (day/month/year) 18 June 1999 (18.06.99)	Priority date (day/month/year) 24 June 1998 (24.06.98)
Applicant KATO, Shinichi et al	

1. The designated Office is hereby notified of its election made:

☒ in the demand filed with the International Preliminary Examining Authority on:

17 January 2000 (17.01.00)

☐ in a notice effecting later election filed with the International Bureau on:2. The election ☒ was☐ was not

made before the expiration of 19 months from the priority date or, where Rule 32 applies, within the time limit under Rule 32.2(b).

The International Bureau of WIPO 34, chemin des Colombettes 1211 Geneva 20, Switzerland	Authorized officer Diana Nissen
Facsimile No.: (41-22) 740.14.35	Telephone No.: (41-22) 338.83.38

TENT COOPERATION TRE

RECEIVED 3 0 AUG 1999

PCT

**NOTIFICATION CONCERNING
SUBMISSION OR TRANSMITTAL
OF PRIORITY DOCUMENT**

(PCT Administrative Instructions, Section 411)

From the INTERNATIONAL BUREAU

To:

YANAGIDA, Masashi
Yanagida & Associates
7F, Benex S-1
3-18-20, Shin-Yokohama
Kohoku-ku, Yokohama-shi
Kanagawa-ken 222-0033
JAPON

Date of mailing (day/month/year) 16 August 1999 (16.08.99)	IMPORTANT NOTIFICATION
Applicant's or agent's file reference PA3934PCT	
International application No. PCT/JP99/03247	
International publication date (day/month/year) Not yet published	
International filing date (day/month/year) 18 June 1999 (18.06.99)	Priority date (day/month/year) 24 June 1998 (24.06.98)
Applicant FUJI PHOTO FILM CO., LTD. et al	

- The applicant is hereby notified of the date of receipt (except where the letters "NR" appear in the right-hand column) by the International Bureau of the priority document(s) relating to the earlier application(s) indicated below. Unless otherwise indicated by an asterisk appearing next to a date of receipt, or by the letters "NR", in the right-hand column, the priority document concerned was submitted or transmitted to the International Bureau in compliance with Rule 17.1(a) or (b).
- This updates and replaces any previously issued notification concerning submission or transmittal of priority documents.
- An asterisk(*) appearing next to a date of receipt, in the right-hand column, denotes a priority document submitted or transmitted to the International Bureau but not in compliance with Rule 17.1(a) or (b). In such a case, **the attention of the applicant is directed** to Rule 17.1(c) which provides that no designated Office may disregard the priority claim concerned before giving the applicant an opportunity, upon entry into the national phase, to furnish the priority document within a time limit which is reasonable under the circumstances.
- The letters "NR" appearing in the right-hand column denote a priority document which was not received by the International Bureau or which the applicant did not request the receiving Office to prepare and transmit to the International Bureau, as provided by Rule 17.1(a) or (b), respectively. In such a case, **the attention of the applicant is directed** to Rule 17.1(c) which provides that no designated Office may disregard the priority claim concerned before giving the applicant an opportunity, upon entry into the national phase, to furnish the priority document within a time limit which is reasonable under the circumstances.

<u>Priority date</u>	<u>Priority application No.</u>	<u>Country or regional Office or PCT receiving Office</u>	<u>Date of receipt of priority document</u>
24 June 1998 (24.06.98)	10/176894	JP	06 Augu 1999 (06.08.99)

The International Bureau of WIPO
34, chemin des Colombettes
1211 Geneva 20, Switzerland

Facsimile No. (41-22) 740.14.35

Authorized officer

Marc Salzman

Telephone No. (41-22) 338.83.38





P.B.5818 - Patentlaan 2
2280 HV Rijswijk (ZH)
☎ +31 70 340 2040
TX 31651 epo nl
FAX +31 70 340 3016

Europäisches
Patentamt

Zweigstelle
in Den Haag
Recherchen-
abteilung


European
Patent Office

Branch at
The Hague
Search
division

Offic européen
des brevets

Département à
La Haye
Division de la
recherche

Klunker . Schmitt-Nilson . Hirsch
Winzererstrasse 106
80797 München
ALLEMAGNE



Datum/Date

19.04.02

Zeichen/Ref./Réf.

K 54 307/7nb

Anmeldung Nr./Application No./Demande n°/Patent Nr./Patent No./Brevet n°.

02001784.4-2210-

Anmelder/Applicant/Demandeur/Patentinhaber/Proprietor/Titulaire

FUJI PHOTO FILM CO., LTD.

COMMUNICATION

The European Patent Office herewith transmits as an enclosure the European search report for the above-mentioned European patent application.

If applicable, copies of the documents cited in the European search report are attached.

☒ Additional set(s) of copies of the documents cited in the European search report is (are) enclosed as well.

The following specifications given by the applicant have been approved by the Search Division:

☐ abstract

☒ title

☒ The abstract was modified by the Search Division and the definitive text is attached to this communication.

The following figure will be published together with the abstract: 10A, 10B

REFUND OF THE SEARCH FEE

If applicable under Article 10 Rules relating to fees, a separate communication from the Receiving Section on the refund of the search fee will be sent later.





DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	US 5 705 004 A (WATANABE SEIICHI) 6 January 1998 (1998-01-06) * column 2, line 66 - column 4, line 61; figures *	1, 3, 4	G11B23/03 G11B23/033 G11B23/50
A	US 5 687 048 A (MIZUTA AKIRA) 11 November 1997 (1997-11-11) * column 4, line 35 - column 5, line 67; figures *	1	
A	EP 0 309 727 A (POLAROID CORP) 5 April 1989 (1989-04-05) * column 11, line 33 - column 13, line 36; figures *	1	
A	PATENT ABSTRACTS OF JAPAN vol. 096, no. 012, 26 December 1996 (1996-12-26) -& JP 08 203234 A (FUJI PHOTO FILM CO LTD), 9 August 1996 (1996-08-09) * abstract; figures *	1	
A	DE 39 41 334 A (FUJI PHOTO FILM CO LTD) 21 June 1990 (1990-06-21) * column 5, line 46 - column 6, line 45; figures *	1	
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 22 March 2002	Examiner Declat, M
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons ----- & : member of the same patent family, corresponding document	

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 02 00 1784

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

22-03-2002

Patent document cited in search report		Publication date	Patent family member(s)		Publication date
US 5705004	A	06-01-1998	JP	8221943 A	30-08-1996
US 5687048	A	11-11-1997	JP	8221930 A	30-08-1996
EP 0309727	A	05-04-1989	US	4814926 A	21-03-1989
			AT	73956 T	15-04-1992
			AU	2281588 A	06-04-1989
			BR	8803981 A	02-05-1989
			CA	1312949 A1	19-01-1993
			CN	1032463 A , B	19-04-1989
			DE	3869305 D1	23-04-1992
			DE	309727 T1	03-08-1989
			DK	536988 A	29-03-1989
			EP	0309727 A1	05-04-1989
			GR	89300108 T1	19-01-1990
			JP	1125778 A	18-05-1989
			KR	131770 B1	15-04-1998
			MX	164885 B	30-09-1992
			NO	883445 A	29-03-1989
			PT	88382 A	31-07-1989
JP 08203234	A	09-08-1996	NONE		
DE 3941334	A	21-06-1990	JP	2167636 A	28-06-1990
			JP	2542249 B2	09-10-1996
			DE	3941334 A1	21-06-1990
			US	5012569 A	07-05-1991